

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 7,028,289 B2
APPLICATION NO. : 09/977507
DATED : April 11, 2006
INVENTOR(S) : David S. Allison

Page 1 of 17

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

On the Title Page

A drawing was erroneously omitted. Applicant respectfully requests a drawing be inserted on the bottom of the coversheet. Insert Figure 12

In the Drawings:

Please delete Drawing sheets 1 thru 15 and replace with the attached fifteen drawings.

Signed and Sealed this

Seventeenth Day of October, 2006

A handwritten signature in black ink, reading "Jon W. Dudas". The signature is stylized, with a large loop for the "J" and a cursive "Dudas".

JON W. DUDAS
Director of the United States Patent and Trademark Office

(12) **United States Patent**
Allison

(10) Patent No.: **US 7,028,289 B2**
(45) Date of Patent: **Apr. 11, 2006**

(54) **STREAM OPERATOR IN A DYNAMICALLY TYPED PROGRAMMING LANGUAGE**

(75) Inventor: **David S. Allison, San Ramon, CA (US)**

(73) Assignee: **Sun Microsystems, Inc., Santa Clara, CA (US)**

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 809 days.

(21) Appl. No.: **09/977,507**

(22) Filed: **Oct. 12, 2001**

(65) **Prior Publication Data**

US 2003/0093592 A1 May 15, 2003

(51) Int. Cl. **G06F 9/44** (2006.01)

(52) U.S. CL. **717/114; 717/159**

(58) Field of Classification Search **717/114, 717/159**

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,450,600 A * 9/1995 Abe 717/114
5,598,560 A * 1/1997 Benson 717/159
6,134,707 A * 10/2000 Herrmann et al. 717/139
6,138,273 A * 10/2000 Sturges 717/114

OTHER PUBLICATIONS

Microsoft GW-BASIC Interpreter User's Guide, Microsoft Corporation, 1988, pp. 10-16, 38-45, 51-55, 61-70, 91-98.*

Using Basic, Rich Didday, West Publishing, 1981, pp. 416-420.*

Fast Power Estimation For Deterministic Input Streams, Luca Benini et al, IEEE, 1997, pp. 494-501.*

Efficient Power Estimation for Highly Correlated Input Streams, Radu Marculescu et al, ACM, 1995, 7 pages.*

UIO: A Uniform I/O System Interface for Distributed Systems, David R. Cheriton Stanford University, ACM, vol. 5, No 1, Feb. 1987, pp. 12-46.*

Testing and Spot-Checking of Data Streams, J. Feigenbaum et al, ACM, 1997, pp. 165-174.*

The Multics Input/Output System, R.J. Feirtag, MIT, ACM 1971, pp. 35-41.*

Optimal Smoothing Schedules for Real-Time Streams, Yishay Mansour et al, ACM, 2000, pp. 21-29.*

* cited by examiner


Primary Examiner—Todd Ingberg

(74) Attorney, Agent, or Firm—Osha Liang LLP

(57) **ABSTRACT**

The present invention provides a method and apparatus for implementation of an input/output stream operator in a dynamically typed language. This operator is built into the language, and allows a value of one type to be streamed to a value of another type by taking the form fromvalue→tovalue. Since the programming language is dynamic, the type of values on either side of the → operator is of any supported type, and can be modified depending upon the type of operands. For example, a value of any type can be streamed to a value of type "stream". In this instance, the destination value is attached to, for example, a device such as a terminal or disk drive. A value of type "stream" can also be streamed into a value of any type. In this instance an external source is inputted, for example, into a program.

16 Claims, 16 Drawing Sheets








FIG. 1

**FIG. 2**

**FIG. 3**




FIG. 4A






FIG. 4B

U.S. Patent

Apr. 11, 2006

Sheet 5 of 15

7,028,289 B2

**FIG. 5A****FIG. 5B**

U.S. Patent

Apr. 11, 2006

Sheet 6 of 15

7,028,289 B2

Function	Purpose
openin (filename)	Open the named file for input
openout (filename)	Open the named file for output
openup (filename)	Open the names file for update(reading and writing)
openfd (fd)	Open the integer file descriptor as a stream
open (filename, mode)	Open the named file with the given integer mode.

FIG. 6A

Function	Meaning
Network.open (addr,port)	Open an active network connection (TCP)
Network.openServer (addr,port, type)	Open a passive network connection (TCP or UDP)
Network.lookupName (name)	Consult a naming service to convert a network name to an address
Network.lookupAddress (ipaddr)	Consult a naming service to convert an integer IP address into a host name
Network.accept ()	Wait for and accept an incoming connection
Network.openSocket ()	Open a UDP client socket for sending datagrams
Network.send (socket, addr, port, buffer)	Send a UDP datagram to the given socket. The addr and port specify the recipient. The buffer is the string to send
Network.receive (socket, var addr, var port, maxbuffer = 4096)	Wait for an incoming UDP datagram. Blocks until a datagram is received, then returns the data as a string. Also sets the addr and port to the sending address. The maxbuffer argument specifies the max size of data that can be received
Network.peek (socket, var addr, var port, maxbuffer = 4096)	As receive, but don't extract the data from the network. A call to receiver() will read the data.
Network.formatIPAddress (addr)	Build a string of the form n.n.n.n out of an integer IP address.

FIG. 6B

U.S. Patent

Apr. 11, 2006

Sheet 7 of 15

7,028,289 B2

Data type	Reading	Writing
integer	Decimal integer converted to binary	Decimal interger
string	Whole line read - terminated by line feed character which is discarded	Characters written to stream
real	ASCII for real value	Written as ASCII
char	Single character	Single character
vector	Each line of file appended to vector - line feed is retained	Each element written
map	cannot read	Elements written as first = second
enumeration constant	cannot read	Name of enumeration constant

FIG. 7

Operation	Result
close (stream)	The stream is closed.
select (stream, timeout)	Returns 1 if there is data waiting to be read from stream. Times out after timeout microseconds.
eof (stream)	Returns 1 if the stream is at the end of file.
flush (stream)	Flush the data remaining in the stream buffers.
getchar (stream)	Read a single character from the stream. Returns the character read.
getbuffer (stream)	Read all the available characters in the stream buffer. Returns a string containing all the characters.
availableChars (stream)	Returns the number of characters in the buffer.
setStreamAttribute (stream, attr, value)	Set the value of a stream attribute.
rewind (stream)	Rewind the stream to the start.
seek (stream, offset, whence)	Move to a new position in a seekable stream.

FIG. 8

U.S. Patent

Apr. 11, 2006

Sheet 8 of 15

7,028,289 B2

8/15

Output type	Input type	Operation
integer	integer	copy left to right
	real	real converted to integer
	string	string converted to integer if possible, 0 otherwise
	vector	first element converted to integer
	map	first element converted to integer
	char	converted to integer
	block	integer set to address
	enumconst	index into enumeration
	object	call toInteger() if present, otherwise address of object
	stream	one integer read from stream
real	integer	converted to real
	real	copied
	string	string converted to real if possible, 0.0 otherwise
	vector	first element converted to real
	map	first element converted to real
	char	converted to integer then real
	block	converted to integer then real
	enumconst	converted to integer then real
	object	toReal() called if present, error otherwise
	stream	one floating point number read from stream
string	integer	converted to string
	real	converted to string
	string	copied
	vector	each element appended to string
	map	each element appended to string
	char	converted to string
	block	name of block
	enumconst	name of constant
	object	toString() called if present, <u>blockname@address</u> if not
	stream	one line read from stream
char	integer	truncated to 8 bits
	real	runtime error
	string	first character in string
	vector	first element converted to char
	map	first element converted to char
	block	first character of name
	enumconst	'A' = first const, 'B' = second, etc
	object	toChar() called if present, error if not
	stream	one char read from stream

FIG. 9A

U.S. Patent


Apr. 11, 2006


Sheet 9 of 15

7,028,289 B2

Output type	Input type	Operation
vector	object	toVector() called if present, otherwise object appended to vector
	anything	appended to vector
map	object	toMap() called if present, otherwise appended
	anything	appended as {x =x}
function	scalar	function called with single argument
	vector	function called once for each element. Element passed as parameter
	map	Function called for each element. Function has to arguments for left and right of map pair.
	stream	function called for each line of input
thread		like function
class		like function only new object created for each
package		like class
enum		runtime error
enumconst		runtime error
object		runtime error
stream	integer	converted to decimal character sequence
	real	converted to floating point character sequence
	string	each character written
	char	single character written
	vector	each element written
	map	each element written as left = right
	block	block name written
	enumconst	name of constant written
	object	"object" + address written
	stream	stream copied

FIG. 9B



**FIG. 11**




FIG. 12





FIG. 13


U.S. Patent

Apr. 11, 2006

Sheet 14 of 15

7,028,289 B2

**FIG. 14**

**FIG. 15**